


## Artikelnummer/Itemnumber: 460FU

Absperrpfosten Stahlrohr Ø 60 x 2,5 mm umlegbar mit Dreikantverschluss, für Dübelbefestigung mit Bodenplatte 100 x 150 mm, feuerverzinkt, ohne Öse

Barrier posts Steel tube Ø 60 x 2,5 mm foldable with triangular locking mechanism, to be fixed by plugs with base plate 100 x 150 mm, hot-dip galvanized, without eyelet



### Artikelbeschreibung:

Absperrpfosten Stahlrohr Ø 60 x 2,5 mm mit aufgeschweißter Stahlkappe 900 mm Überflur umlegbar, mit Dreikantverschluss nach DIN 3223, selbsteinrastende Verriegelung, für Dübelbefestigung mit Bodenplatte 100 x 150 mm, feuerverzinkt, ohne Öse

### Verwendungszweck:

Absperrpfosten zur Sperrung von Gehwegen für Fahrzeuge, außerdem zur Wegbegrenzung.

### Technische Daten:

Gewicht: 6,50 kg/St  
Material:  
Stahl S235 JR

Oberfläche:  
Feuerverzinkung nach DIN ISO 1461

### item description:

Barrier posts Steel tube Ø 60 x 2.5 mm with welded steel cap 900 mm above ground Foldable, with triangular locking mechanism acc. With DIN 3223, self-engaging lock, to be fixed by plugs with base plate 100 x 150 mm, hot-dip galvanized, without eyelet

### designated purpose:

Barrier posts for closing off sidewalks for vehicles, also for limiting paths.

### technical specifications:

weight: 6,50 kg/pc  
material:  
S235 JR

surface:  
hot dipped galvanized acc. to DIN ISO 1461